



Weighing Terminal HTF200

simple | compact | calibratable

Benefits:

- Universal use
- High operational security
- Calibratable
- Database connection is possible
- Internal rechargeable battery is possible
- Simple operation

Technical Data

HTF200 is suitable for difficult environmental conditions and locations with high hygienic standards, as in the food, pharmaceutical and chemical industry.

High Operational Security

Fast and error-free operation is ensured by a high-contrast alphanumeric LCD for the indication of weight, IDs and operator prompts in combination with an easy-to-use keyboard.

Weighing Program

Display of net, tare and gross weight. Operator prompting for capturing of weight or piece count.

Data Logging

Via optional printer interface. The print layout for labels or forms is configurable. Printout of weights, totals, date, time and consecutive-number.

Data Transmission To PC

Via optional PC interface. Transmission of date, time, consecutive-number and weight after each weighing cycle.

PC ONLINE Mode


Via optional PC interface. Reading of weight, taring, zero setting and other functions can be remotely controlled from a PC.

Switching And Filling

With an optional input/output module two weight thresholds can be monitored, eg formax. or min. values. Start of weighing cycle and taring is possible from external switches. Alternatively the inputs and outputs can be used for a filling sequence with start/stop/interrupt and two-speed cut-off.

Ex version

With ATEX approval for installation in hazardous area, zone 2 (gas) or zone 22 (dust) available as option.



	Serial interface (maximum of 4)			Digital/analog interface	
	R 232	RS 485	RS 422	Opto-isolated I/Os 24VDC (2/2 oder 1/3)	15-bit analog I/Os (maximum of 1)
Printer	■	■	■		
Remote indication	■	■			
SPS system				■	■
PC/Network	■	■	■		
Externally ethernet module	■	■	■		



Höfelmeyer Waagen GmbH | Georgsmarienhütte | Hufingen | Neuss | Hamburg | Berlin | Leipzig
 Fon +49 5401 4977 0 | Fax +49 5401 4977 90 | waagen@hoefelmeyer.de | www.hoefelmeyer.de

Specifications subject to change without notice.