



# weighing terminal HTF300

robust | flexible | can be calibrated

## Advantages







- Ethernet connection and Profibus can be integrated
- LCD display with background illumination
- Standard programs included
- Database connection possible
- Data transmission to a PC
- Online user interface possible

# The Flexible One!

The HTF300 is a robust industrial terminal in a stainless steel housing for classical use in filling or removal processes, inspection or counting tasks and for vehicle weighing. Typical application areas are goods inward, dispatch, filling, silos or tank storage and production.

## Features

- Wall-mounting, tabletop and build-in versions
- Protection category IP67/IP69K
- Very legible 20 character LCD text display, with background illumination, 14 mm character height
- Integrated alphanumeric keyboard through multiple use of keys and function keys
- Coupling to PLC or control system via Profibus DP in the "AP" version
- Powered via integrated 110-240 VAC or 12-30 VDC supply
- Operating temperature: -10 to +40°C at 95% rel. humidity
- PC software to design printouts
- Safety: Data protected from power failure, password protection, internal alibi memory
- Ex explosion protected versions possible
- Modular interface concept
- For mobile use, optional data transmission via WLAN or Bluetooth (external)
- Remote diagnostics possible



	serial interfaces (max. 2)		Digital/analog interfaces		Field bus	Ethernet
	RS 232	RS 485	Optoisolated inputs/outputs 24 VDC (max. 4)	15 bit analog output	Profibus DPVO 12 MBit/s	10/100 Base-T Ethernet with inte- gr. web server
Relay/transistor coupling (max. 64 inputs/outputs)		■				
Modular analog interface (max. 32 inputs/outputs)		■				
Printer	■	■				
Precision scales	■	■				
Remote display	■	■		■		
PLC system			■	■	■	
PC/network	■					■

\*Only in the "AP" version



Höfelmeyer Waagen GmbH | Georgsmarienhütte | Hüfingen | Neuss | Hamburg | Berlin | Leipzig  
Tel. +49 5401 4977 0 | Fax +49 5401 4977 90 | waagen@hoefelmeyer.de | www.hoefelmeyer.de

We reserve the right to make changes.