



weighing terminal HTF60E

freely programmable | can be calibrated | compact

Advantages

- Ethernet and USB connection on board
- WLAN can be integrated
- Fast, up to date processor technology
- Bright TFT display
- Direct access to files in a PC network
- Customer-specific modifications possible
- Modular interface concept

W1		53.0 Net kg	
Tara		408.5 kg	
Behälteranzahl: 4			
Be. 1	Be. 2	Be. 3	Be. 4
98.0	82.5	76.0	22.0
3	3	3	2
			kg
			Komp
Speichern		Farbig	

W1		183.6 kg	
Tara		0.0 kg	
Verladung von Auftr. A2010/002756			
Produkt		120 Quarzsand	
Kunde		211 Bolla Schiffahrt GmbH	
Ø	12708 kg/h	Sollwert	100000.0 kg
Schütt	78	Ges.	30421.5 kg
Füllen...			
Solwert		Stop	Abbr

The small, compact terminal

The HTF60E is suited, above all, for applications in the chemical and pharmaceutical industry as well as in the food sector. It is primarily used in the following areas: as goods inwards or dispatch scales, as delivery or shipping scales, for dispensing systems, vehicle scales or mobile weighing systems.

Features

- Wall-mounting, tabletop and build-in versions in protection class IP 65 or IP 69K
- Remote diagnostics possible
- Integrated keyboard, function keys and soft-keys
- Powered via integrated 110-240 VAC or 12-30 VDC supply
- Operating temperature: -10 to +40°C at 95% rel. humidity
- 32 bit ARM processor, 266 MHz
- 0.5 MB memory (extensible)
- Real time multitasking operating system based on Linux
- Safety: Data protected from power failure, password protection, internal alibi memory
- PC software to design printouts



	Serial interfaces (max. 2)		Digital/analog interfaces (max. 4)		Field bus	Ethernet		USB 2.0
	RS 232	RS 485	Optoisolated inputs/outputs 24 VDC (max. 4)	15 bit analog input/output (max. 2)	ModBus TCP	10/100 Base-T Ethernet with integr. web server	WLAN	
Relay/transistor coupling (max. 64 inputs/outputs)		■						
Modular analog interface (max. 32 inputs/outputs)		■						
Printer	■	■				■		■
Precision scales	■	■						
Remote display	■	■						
Transponder reader	■	■						
Scanner/keyboard	■							■
PLC system			■	■	■	■		
PC/network						■	■	

Other options on request.



Höfelmeyer Waagen GmbH | Georgsmarienhütte | Hüfingen | Neuss | Hamburg | Berlin | Leipzig
 Tel. +49 5401 4977 0 | Fax +49 5401 4977 90 | waagen@hoefelmeyer.de | www.hoefelmeyer.de

We reserve the right to make changes.