



HTF220 weighing terminal

sturdy | reliable | durable

Advantages

- Extended LCD display with background illumination and bar graph
- Suitable for universal use
- Suitable for industrial applications
- Extendable applications
- User-friendly operation via industrial membrane keypad

For daily quality checks

The HFT220 weighing terminal is a sturdy evaluation unit for demanding daily quality checks. It meets the maximum requirements regarding the reliability of weighing results, particularly in application areas in the food, pharmaceutical, chemical and metal industries. The selectable application programs allow for optimum use based on the respective requirements.

Version

- As a wall-mounted, tabletop or built-in version in protection class IP 65

- Easily legible 20mm LCD plain text display, with background illumination, with bar graph
- Integrated alphanumeric keyboard through multiple use of keys and function keys
- Powered via integrated 100-240V AC power supply
- Optionally 24V DC or 24V AC via internal or external battery pack
- Operating temperature: -10 to +40°C
- Made completely of stainless steel (1.4301)
- Printer can be connected

	Serial interfaces (max. 2)			Digital/analog interfaces	
	RS 232	RS 485	RS 422	Opto-insulated inputs/outputs (relay box)	Analog 0-20mA, 4-20mA, 0-10V, 16 bit
PC/network	2	2	2		
Printer	2	2	2		
PLC system (control)				4 (5) in / 1 out	1

